

**OCONTO COUNTY HIGHWAY DEPARTMENT
OCONTO, WI 54153**

BID SPECIFICATIONS FOR TWO (2) NEW CURRENT PRODUCTION MODEL 2-3 YARD DUMP BODIES & HYDRAULICS

Minimum specifications for two (2) new current production model 2-3 yard dump bodies and hydraulics.

Only bids on bid forms furnished by Oconto County Highway Department will be accepted for award purposes. All bids must be sealed and shall be so indicated on the face of the envelope.

Oconto County Highway Department will receive bids for the furnishing and delivery of the above listed equipment. Bids shall be submitted on forms provided by and addressed to the Oconto County Highway Department, 202 Van Dyke Street, Oconto, WI 54153. Bids will be received up to 11:00 A.M. on Wednesday, February 18, 2015 at the Highway Office in Oconto. Bid opening is scheduled for 11:00 A.M. on Wednesday, February 18, 2015.

These specifications are a part of the bid and must remain attached to the bid. Manufacturer's full and detailed cuts and specifications for the equipment proposed must be attached. All supplies or equipment sold to Oconto County shall be sold at the risk of the contractor or seller until accepted by Oconto County. Terms of agreement: No payment will be made until after inspection and acceptance by Oconto County or its agent.

Oconto County reserves and has the right to reject any or all bids submitted or to accept any part or combination thereof, to waive any technicalities, and to accept bid deemed most advantageous to Oconto County.

All bids shall be firm bids.

All transportation expenses for delivery, mounting, warranty, etc. are the responsibility of the bidder.

Delivery date will be considered in award of bid.

An authorized representative of Oconto County will publicly open all bids – by order of the Oconto County Highway Committee.

Patrick J. Scanlan,
Highway Commissioner

OCONTO COUNTY HIGHWAY DEPARTMENT

FOR BID AND MINIMUM SPECIFICATIONS FOR TWO (2) NEW – 2-3 YARD DUMP BODIES AND HYDRAULICS.

SPECIFICATIONS

SCISSORS DUMP HOIST

Class 20 Hoist
10 ton capacity
Grease zerks at all pivot points
2" chromed and polished cylinder piston rod
Integral body prop
Heavy structural angle rear hinge
Double acting cylinder
Electrical hydraulic driven pump push button control
Installed with push button electrical control

DUMP BODY 2-3 YARD

8' 3" x 88" outside width dump body, 78" inside width

12" tall sides / 10 Gauge HI – Tensile Steel with fully boxed dirt – shedding top rail, and 2 vertical side posts with drain holes. 45 degree sloped rub rail, 2" x 5" side board pockets – sides must fold down.

10 Gauge HI – Tensile Steel Floor with radius corners, supported by 5" structural steel channel long sills, 3" structural steel channel cross sills on 16" centers

18" tall double acting 10 degree inward sloping tailgate constructed 10 Gauge HI Tensile Steel, tailgate recessed flush with rear face of 12" x 4 1/2" full height corner posts, fully boxed tailgate perimeter with two vertical boxes, 1" upper and lower tail gate pins with ez-latch top pin release, no loose pins, forward control trip handle with rubber grip

All LED strobe lamps must be model 60 or equivalent.

Recessed LED stop tail, directional lights mounted in rear posts. Recessed shock resistant rubber clearance lights.

2 LED strobes mounted on rear box.

2 LED strobe lamps mounted under tailgate as wide as possible.

4 LED strobes in cab guard. 2 facing forward and 2 rear ward.

2 Clear LED Strobes in front bumper.

Star ADH 250 top light mounted to cab protector

Sloped ¼ cab shield

Back up alarm

Primed and painted to match truck

Heavy duty rear mud flaps

OPTIONAL EQUIPMENT – TO BE INCLUDED

Roof mounted halogen flood light with control handle – 50 watt

KNAP – PACK OR EQUIVILANT STORAGE

24" long x 55" high x 82" deep

24" long x 14" toolbox

Tapered profile to conform to cab

Heavy duty 14 gauge all galvanneal steel construction

Exclusive all stainless steel door hinge is pry-proof, features a built in weather shield and provides full length door support

Double panel 20 gauge reinforced galvanneal door panels

Full perimeter "uninterrupted" automotive type door seals

Key lockable T – Handle twist latch

Two (2) stationary shelves in main compartment with easy access from either side

Four (4) combination stationary / swivel material hooks

Guaranteed against rust through for five years

465 LB approximate weight

Painted to match truck

All equipment to be mounted on 15,000 GVW chassis of trucks provided by the Oconto County Highway Department

**OCONTO COUNTY HIGHWAY DEPARTMENT
2 – 2-3 YARD DUMP BODIES & HYDRAULICS**

Bid Opening: 11:00 a.m. on Wednesday, February 18, 2015 at the Oconto Highway Office, located at 202 Van Dyke Street ó Oconto, WI

Make and Model of Dump Bodies & Hydraulics: _____

Completion Date for Delivery to Oconto County Highway Department: _____

Net Price Installed of 2 units: _____

Net Price Dump Bodies, Hydraulics, and Storage Box delivered to Suring Shop (Components ONLY):

Bidder to State Warranty: _____

Company Name: _____

Address: _____

Company Representative: _____

(Please Print)

Signature: _____

Date: _____